



Model	60 EF1
Kilowatts	44.1 kW
Max. RPM at Full Throttle	5500-6000
Cylinders	4 (in-line)
Displacement	995 cc
Starting	Electric (turn-key)
Gear Ratio	1.83:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	18 amp (223 watt)
Trim Positions	Power trim standard
Fuel Tank	Standard 25 L
Fuel Requirements	Unleaded 90 RON min.
Weight	112 kg
Recommended Boat Transom Height	508 mm (L)
Induction System	2-valve single overhead cam design
Counter Rotation	N/A



Model	80 EF1
Kilowatts	58.8 kW
Max. RPM at Full Throttle	5000-6000
Cylinders	4 (in-line)
Displacement	1732 cc
Starting	Electric (turn-key)
Gear Ratio	2.33:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	Fully regulated Belt-Driven 50 amp (630 watt)
Trim Positions	Power trim standard
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	181 kg
Recommended Boat Transom Height	508 mm (L)
Induction System	4-valve dual overhead cam design
Counter Rotation	N/A



Model	115 EF1
Kilowatts	84.5 kW
Max. RPM at Full Throttle	5800-6400
Cylinders	4 (in-line)
Displacement	1732 cc
Starting	Electric (turn-key)
Gear Ratio	2.07:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	Fully regulated Belt-Driven 50 amp (630 watt)
Trim Positions	Power trim standard
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	181 kg
Recommended Boat Transom Height	508 mm (L) - 635 mm (XL)
Induction System	4-valve dual overhead cam design
Counter Rotation	N/A



Model	115 OptiMax
Kilowatts	84.5 kW
Max. RPM at Full Throttle	5000-5750
Cylinders	3 (in-line)
Displacement	1526 cc
Starting	Electric (turn-key)
Gear Ratio	2.07:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	Belt-Driven 60 amp (756 watt)
Trim Positions	Power trim standard
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	170 kg
Recommended Boat Transom Height	508 mm (L) - 635 mm (XL)
Induction System	2-stage direct fuel injection
Counter Rotation	N/A



Model	Verado 150
Kilowatts	110 kW
Max. RPM at Full Throttle	5800-6400
Cylinders	4 (in-line)
Displacement	1732 cc
Starting	Electric (turn-key)
Gear Ratio	2.08:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	Fully regulated Belt-Driven 70 amp (882 watt)
Trim Positions	Power trim and tilt with SmartCraft-programmable tilt
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	231 kg
Recommended Boat Transom Height	508 mm (L) - 635 mm (XL)
Induction System	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control
Counter Rotation	Available on XL models



Model	NEW Verado 200
Kilowatts	147 kW
Max. RPM at Full Throttle	5800-6400
Cylinders	4 (in-line)
Displacement	1732 cc
Starting	Electric (turn-key)
Gear Ratio	2.08:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Remote
Alternator System	Fully regulated Belt-Driven 70 amp (882 watt)
Trim Positions	Power trim and tilt with SmartCraft-programmable tilt
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	231 kg
Recommended Boat Transom Height	508 mm (L) - 635 mm (XL)
Induction System	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control
Counter Rotation	Available on XL models



Model	Verado 250
Kilowatts	183 kW
Max. RPM at Full Throttle	5800-6400
Cylinders	6 (in-line)
Displacement	2598 cc
Starting	Electric (turn-key)
Gear Ratio	1.85:1
Gear Shift	Forward (F) - Neutral (N) - Reverse (R)
Steering	Electro-hydraulic Power steering with integral hydraulic cylinder
Alternator System	Fully regulated Belt-Driven 70 amp (882 watt)
Trim Positions	SmartCraft-programmable Power trim and tilt
Fuel Tank	Optional
Fuel Requirements	Unleaded 90 RON min.
Weight	288 kg
Recommended Boat Transom Height	508 mm (L) - 635 mm (XL) - 762 mm (XXL)
Induction System	SmartCraft DTS (Digital Throttle & Shift), supercharged with charge air cooling and electronic boost pressure control
Counter Rotation	Available on XL and XXL models